

FLAT ROOF PANEL									TRIMDECK ROOF PANEL									INSUL ROOF PANEL								
MAXIMUM SPAN FOR WIND CLASS - C1									MAXIMUM SPAN FOR WIND CLASS - C1									MAXIMUM SPAN FOR WIND CLASS - C1								
PANEL THICKNESS	50	75	100	125	150	175	200	250	PANEL THICKNESS	50	75	100	125	150				PANEL THICKNESS	50	75	100	125	150	175	200	
STAND ALONE	4200	5200	6000	6800	7400	8000	8800	9400	STAND ALONE	5000	6200	6800	7400	8000				STAND ALONE	4200	5200	6000	6800	7400	8000	8800	
OPEN 3 SIDES	4000	4800	5600	6400	7000	7600	8400	9000	OPEN 3 SIDES	5000	6000	6600	7000	7800				OPEN 3 SIDES	4000	4800	5600	6400	7000	7600	8400	
OPEN 2 SIDES	3200	4000	4600	5200	5600	6200	6800	7400	OPEN 2 SIDES	4200	4800	5400	6000	6400				OPEN 2 SIDES	3200	4000	4600	5200	5600	6200	6800	
FULLY ENCLOSED	3000	3800	4400	4800	5400	5800	6400	7000	FULLY ENCLOSED	4000	4600	5200	5600	6000				FULLY ENCLOSED	3000	3800	4400	4800	5400	5800	6400	
MAX CANTILEVER	700	850	1100	1300	1500	1700	1900	2100	MAX CANTILEVER	800	1000	1200	1400	1600				MAX CANTILEVER	700	850	1100	1300	1500	1700	1900	
MAXIMUM SPAN FOR WIND CLASS - C2									MAXIMUM SPAN FOR WIND CLASS - C2									MAXIMUM SPAN FOR WIND CLASS - C2								
PANEL THICKNESS	50	75	100	125	150	175	200	250	PANEL THICKNESS	50	75	100	125	150				PANEL THICKNESS	50	75	100	125	150	175	200	
STAND ALONE	3600	4400	5200	5800	6400	7000	7600	8200	STAND ALONE	4400	5400	6000	6600	7200				STAND ALONE	3600	4400	5200	5800	6400	7000	7600	
OPEN 3 SIDES	3400	4200	4800	5400	6000	6600	7200	7800	OPEN 3 SIDES	4400	5200	5800	6200	6800				OPEN 3 SIDES	3400	4200	4800	5400	6000	6600	7200	
OPEN 2 SIDES	2800	3400	4000	4400	4800	5400	6000	6600	OPEN 2 SIDES	3600	4200	4800	5200	5600				OPEN 2 SIDES	2800	3400	4000	4400	4800	5400	6000	
FULLY ENCLOSED	2600	3200	3800	4200	4600	5000	5600	6200	FULLY ENCLOSED	3400	3800	4400	4800	5200				FULLY ENCLOSED	2600	3200	3800	4200	4600	5000	5600	
MAX CANTILEVER	700	850	1100	1300	1500	1700	1900	2100	MAX CANTILEVER	800	1000	1200	1400	1600				MAX CANTILEVER	700	850	1100	1300	1500	1700	1900	
MAXIMUM SPAN FOR WIND CLASS - C3									MAXIMUM SPAN FOR WIND CLASS - C3									MAXIMUM SPAN FOR WIND CLASS - C3								
PANEL THICKNESS	50	75	100	125	150	175	200	250	PANEL THICKNESS	50	75	100	125	150				PANEL THICKNESS	50	75	100	125	150	175	200	
STAND ALONE	3200	3800	4400	5000	5400	6000	6600	7200	STAND ALONE	3600	4400	5000	5400	6000				STAND ALONE	3200	3800	4400	5000	5400	6000	6600	
OPEN 3 SIDES	3000	3600	4200	4800	5200	5600	6200	6800	OPEN 3 SIDES	3400	4000	4600	5000	5400				OPEN 3 SIDES	3000	3600	4200	4800	5200	5600	6200	
OPEN 2 SIDES	2600	3000	3400	3800	4200	4600	5200	5800	OPEN 2 SIDES	3400	3600	4000	4400	4800				OPEN 2 SIDES	2600	3000	3400	3800	4200	4600	5200	
FULLY ENCLOSED	2200	2800	3200	3600	4000	4400	4800	5400	FULLY ENCLOSED	3000	3400	3800	4200	4400				FULLY ENCLOSED	2200	2800	3200	3600	4000	4400	4800	
MAX CANTILEVER	700	850	1100	1300	1500	1700	1900	2100	MAX CANTILEVER	800	1000	1200	1400	1600				MAX CANTILEVER	700	850	1100	1300	1500	1700	1900	



123 ENTERPRISE STREET
 BOHLE QLD 4818
 PHONE (07) 47744983
 FAX (07) 47744986

NORFOAM SPAN TABLE
 INSULATED PANEL
 Drawing Number: 601-2

Engineering Certification

**CERTIFIED AS
 STRUCTURALLY ADEQUATE**

MOODIE ENGINEERING P/L
 Engineers, Planners and Project Managers
 16-18 Lake Placid Rd, Cairns
 PO Box 487, Smithfield Q 4878
 Date: 18-9-2014 Signed: *Audrey R Moodie*
 Job No: 1409NORFOAM RPEQ No: 7450